

INDOOR LEDWALLS

Specifications

Pixel pitch	0.9	1.2	1.5	1.8	2	2.5
LED configuration	IMD 4 in 1	SMD1010	SMD1212	SMD1515	SMD1515	SMD1515
Panel size (mm)	600 x 337.5	600 x 337.5	600 x 337.5	600 x 337.5	600 x 337.5	600 x 337.5
Ratio	16:9	16:9	16:9	16:9	16:9	16:9
Material	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
Panel weight (Kg)	3.8	3.8	3.8	3.8	3.8	3.8
Thickness (mm)	22.5	22.5	22.5	22.5	22.5	22.5
Maintenance	Front	Front	Front	Front	Front	Front
Brightness (Nits)	600	600	600	600	600	600
Viewing angle	170° / 160°	170° / 160°	170° / 160°	170° / 160°	170° / 160°	170° / 160°
Refresh rate (Hz)	> 3840	> 3840	> 3840	> 3840	> 3840	> 3840
Max power consumption (W)	145	145	145	145	145	145
Average power consumption (W/sqm)	48	48	48	48	48	48
Life span (h)	> 100,000	> 100,000	> 100,000	> 100,000	> 100,000	> 100,000
IP rating (front/back)	IP31 / IP31	IP31 / IP31	IP65 / IP54	IP65 / IP54	IP65 / IP54	IP65 / IP54