

OUTDOOR LEDWALLS

Specifications

Pixel pitch	2.5	3	4	5	6.6	8	10
LED configuration	SMD1415	SMD1415	SMD1921	SMD2727	SMD2727	SMD2727	SMD3535
Panel size (mm)	960x960	960x960	960x960	960x960	960x960	960x960	960x960
Ratio	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Panel weight (Kg)	30	30	25	25	25	25	25
Thickness (mm)	90	90	72	72	72	72	72
Maintenance	Front / rear	Front / rear	Front / rear	Front / rear	Front / rear	Front / rear	Front / rear
Brightness (Nits)	4500	5000	5500	6500	6500	6500	6500
Viewing angle	140° / 120°	140° / 120°	150° / 140°	150° / 140°	150° / 140°	150° / 140°	150° / 140°
Refresh rate (Hz)	> 1280	> 1920	> 1920	> 1920	> 1920	> 1920	> 1920
Max power consumption (W)	800	800	590	590	590	590	590
Average power consumption (W/sqm)	350	350	170	170	170	170	170
Life span (h)	> 100,000	> 100,000	> 100,000	> 100,000	> 100,000	> 100,000	> 100,000
IP rating	IP65	IP65	IP65	IP65	IP65	IP65	IP65